



# Super Heavy Nuclei International Symposium

Texas A&M University, College Station  
Texas, USA

March 31 - April 02, 2015



## On-line separators for SHE Factory

Andrey Popeko  
FLNR JINR

## **Bottom lines:**

### **Universal Gas-filled & Air-free separator:**

- complete fusion reactions;
- multi-nucleon transfer reactions;
- nuclear spectroscopy @ target & focal plane.

### **Preseparator & gas-catcher, RPC-chamber:**

- chemistry;
- fusion and multi-nucleon transfer reactions;
- mass-spectrometry and nuclear spectroscopy;
- laser spectroscopy of heavy atoms.

# **The goal: high production rate of SHE**

- **High beam current;**
- **High transmission;**
- **Reduction of background.**

## What from what?

- SHE;
- Primary beam;
- Target (transfer target-like) products;
- Neutrons;
- High-energy protons or alphas;
- Scattered beam.




## Charge systematics

- V.S. Nikolaev & I.S. Dmitriev, Phys. Lett., 28A(1968)277;
- K. Shima, T. Ishihara & T. Mikumo Nucl. Instr. & Meth., 200(1982)605;
- Yu.Ts. Oganessian *et al.*, Z. Phys. D., 21(1991)357.
- A. Ghiorso *et al.*, Nucl. Inst. & Meth., A269(1988)192.
- Y. Baudinet-Robinet *et al.*, J. Phys. B11(1978)1291.


## Scattering and solving down

- J.F. Ziegler, J.P. Biersack, U. Littmark. *The stopping and range of ions in solids*. V. 1, Pergamon press, 1985.


# Analyzed reactions



# Energy distributions for different target thicknesses





# Angular distributions for different target thicknesses



# Transmission & yield of $^{254}\text{No}$

$^{208}\text{Pb}(^{48}\text{Ca}, 2n)^{254}\text{No}$  (FWHM=10.0 MeV  $\rightarrow$  1.37 mg/cm<sup>2</sup>,  $\sigma$  = 0.583 mg/cm<sup>2</sup>)










| Nucl.                       | E(MeV) | B $\rho$ (vac. T·m) | B $\rho$ (He. T·m) | B $\rho$ (H <sub>2</sub> . T·m) | V (cm/ns) | E/q <sub>vac</sub> (MV) |
|-----------------------------|--------|---------------------|--------------------|---------------------------------|-----------|-------------------------|
| <sup>48</sup> Ca            | 236    | 0.88                | 0.94               | 0.94                            | 3.1       | 13.0                    |
| <sup>292</sup> 114          | 38.8   | 0.79                | 2.0                | 2.18                            | 0.51      | 2.0                     |
| <sup>244</sup> Pu           | 129.7  | 0.83                | 1.65               | 1.49                            | 1.0       | 4.2                     |
| <sup>4</sup> He             | 67     |                     | 1.2                |                                 | 5.7       |                         |
| <sup>1</sup> H <sub>2</sub> | 18.8   |                     |                    | 0.62                            | 6.02      |                         |

# Magnetic rigidities




# **Air-free separator**

# Velocity Filter “SHIP”




# Electrostatic separator VASSILISSA

## 1987 – 2004 – 2012




**$E/q < 2 \text{ MV}$**



# Velocity filter SHELS

(Separator for Heavy ELement Spectroscopy)



$$E/q < 10 \text{ MV}$$



# Movable plates of electrostatic deflectors





# SHELS + GABRIELA




# Gas-filled separator

# GF-separators

| Separator               | DGFRS      | GARIS        | RITU            | BGS         | TASCA      |
|-------------------------|------------|--------------|-----------------|-------------|------------|
| Configuration           | $DQ_h Q_v$ | $DQ_h Q_v D$ | $Q_v D Q_h Q_v$ | $Q_v D_h D$ | $DQ_h Q_v$ |
| Deflection angle (°)    | 23         | 45+10        | 25              | 70          | 30         |
| Bp (max/T·m)            | 3.1        | 2.15         | 2.2             | 2.5         | 2.4        |
| Length (m)              | 4.0        | 5.75         | 4.7             | 4.6         | 3.5        |
| Dispersion<br>(mm/% Bp) | 7.5        | 9.7          | 10.0            | 20.0        | 9.0        |

# Dubna Gas Filled Recoil Separator






# Gas-filled Recoil Separator (RIKEN)



# TransActiniden Separator und Chemie Apparatur (TASCA) (GSI, Darmstadt)






# **Recoil Ion Transport Unit (RITU)** (Jyväskylä, Finland)




# Berkeley Gas-filled Separator





# Spectrometer for Heavy Atom and Nuclear Structure (SHANS) (IMP, Lanzhou)




## Gas-filled separator Advantages:

- presence of a gas –  $H_2$ , He;
- ✓ high energy and charge acceptances;
- ✓ additional target cooling through convection;
- low number of elements;
- no high voltage;
- “low” price.

## Target gas cooling (infra red snap-shots)

$10^{-6}$  mB  
 $P=1.3$  W  
 $T=90-150^{\circ}\text{C}$



0.6 mB He  
 $P=2.7$  W  
 $T=35-150^{\circ}\text{C}$




## Gas-filled separator Disadvantages:

- presence of gas –  $\text{H}_2$ , He;
- ✓ background from high energetic (15 – 60 MeV) light particles;
- ✓ must be short ( $< 5$  m) → difficult to organize shielding;
- ✓ difficult (or impossible) to organize “coming from outside” mark;
- not suitable for very asymmetric reactions;
- not applicable for symmetric reactions;



| Nucl                        | E(MeV) | Bp (vac. T·m) | Bp (He, T·m) | Bp (H <sub>2</sub> , T·m) | V (cm/ns) | E/q <sub>vac</sub> (MV) |
|-----------------------------|--------|---------------|--------------|---------------------------|-----------|-------------------------|
| <sup>22</sup> Ne            | 112.4  | 0.76          | 0.76         | 0.76                      | 3.14      | 11.7                    |
| <sup>260</sup> No           | 9.5    | 0.74          | 1.82         | 2.45                      | 0.26      | 0.99                    |
| <sup>238</sup> U            | 34.8   | 0.72          | 1.89         | 2.01                      | 0.53      | 1.93                    |
| <sup>4</sup> He             | 58.5   |               | 1.1          |                           | 5.3       |                         |
| <sup>1</sup> H <sub>2</sub> | 18.7   |               |              | 0.62                      | 6.0       |                         |

# Gas filled separators for asymmetric combinations






| Nucl.                       | E(MeV) | B $\rho$ (vac. T·m) | B $\rho$ (He. T·m) | B $\rho$ (H <sub>2</sub> . T·m) | V (cm/ns) | E/q <sub>vac</sub> (MV) |
|-----------------------------|--------|---------------------|--------------------|---------------------------------|-----------|-------------------------|
| <sup>136</sup> Xe           | 600    | 1.1                 | 1.38               | 1.38                            | 3.0       | 15.7                    |
| <sup>272</sup> Hs           | 300    | 0.95                | 1.39               | 1.21                            | 1.46      | 6.85                    |
| <sup>136</sup> Xe           | 600    | 1.1                 | 1.38               | 1.38                            | 3.0       | 15.7                    |
| <sup>4</sup> He             | 66.6   |                     | 1.2                |                                 | 5.7       |                         |
| <sup>1</sup> H <sub>2</sub> | 17.4   |                     |                    | 0.6                             | 6.0       |                         |




# Transmission losses in the DGFRS

$(^{243}\text{Am}(^{48}\text{Ca},4n)^{286}115; \text{DQ}_h\text{Q}_v)$




# Universal QDQQD-gas-filled separator




# GICOSY beam plot for $Q_v D Q_h Q_v D$

$^{22}\text{Ne}(112 \text{ MeV}) + ^{238}\text{U}(\text{met}, 0.3 \text{ mg/cm}^2) \rightarrow ^{256}\text{No} + 4n$



# New Gas-Filled Separator

(DANFYSIKs technical drawing, 1.5 years, 1.5 M€)



# Main optical elements of the QDQQD-GFS

## Magnetic quadrupole 1

|                        |        |
|------------------------|--------|
| Effective length       | 370    |
| Bore diameter          | 150 mm |
| Maximum field gradient | 15 T/m |

## Magnetic quadrupole 2 & 3

|                        |        |
|------------------------|--------|
| Effective length       | 520    |
| Bore diameter          | 220 mm |
| Maximum field gradient | 10 T/m |

## Magnetic dipole 1

|                          |        |
|--------------------------|--------|
| Gap                      | 120 mm |
| Deflection angle         | 30°    |
| Radius of curvature      | 1.8 m  |
| Maximum field            | 1.7 T  |
| Face pole rotation angle | 10°    |
| Rear pole rotation angle | 55°    |

## Magnetic dipole 2

|                          |        |
|--------------------------|--------|
| Gap                      | 120 mm |
| Deflection angle         | 10°    |
| Radius of curvature      | 1.8 m  |
| Maximum field            | 1.7 T  |
| Face pole rotation angle | 0°     |
| Rear pole rotation angle | 10°    |




# Transmissions of the QDQQD


| Reaction                                            | Asymmetry<br>$A_p/(A_p+A_t)$ | Transmission<br>% |
|-----------------------------------------------------|------------------------------|-------------------|
| $^{244}\text{Pu}(^{22}\text{Ne},3n)^{263}\text{Rf}$ | 0.083                        | 7.5               |
| $^{244}\text{Pu}(^{48}\text{Ca},3n)^{289}114$       | 0.164                        | 35                |
| $^{244}\text{Pu}(^{58}\text{Fe},4n)^{298}120$       | 0.192                        | 50                |
| $^{70}\text{Zn}(^{208}\text{Pb},1n)^{277}\text{Cn}$ | 0.252                        | 60                |
| $^{93}\text{Kr}(^{226}\text{Ra},1n)^{318}124$       | 0.291                        | 70                |

# Preseparator


# GFS superconducting



# $Q_v D Q_h$ -gas-filled “chemical” pre-separator



# GFS - $Q_v D Q_h$





## Summary & Proposals:

- Velocity selector SHELS
- Universal gas-filled separator  $Q_v D Q_h Q_v D$
- Gas-filled pre-separator  $Q_v D Q_h$





**THANK YOU  
FOR YOUR  
ATTENTION !**

**Flerov Laboratory of Nuclear Reactions (JINR)**